



S2040 Scanner

Affordable, fast and compact scanning

Specifications

Product Highlights	Built to capture information anywhere, with superior image quality and data accuracy, the S2040 is the perfect solution to get information into your business processes quickly
Throughput Speeds *	40 ppm / 80 ipm
Feeder Capacity	Up to 80 sheets of 80 g/m ² (20 lb.) paper
Connectivity	<ul style="list-style-type: none"> ○ USB 3.2 Gen 1x1 <i>USB 3.2 Gen 1x1 = USB 3.1 Gen 1 = USB 3.0 (5Gbps)</i> ○ USB 2.0 compatible
Maximum Document Size <i>The maximum document size supported by the scanner will vary based on the output image resolution and image compression used.</i>	216 mm x 3000 mm (8.5 in. x 118 in.)
Minimum Document Size	52 mm x 52 mm (2.08 in. x 2.05 in.)
Paper Thickness & Weight	<ul style="list-style-type: none"> ○ 27–433 g/m² (7.2–160 lb.) paper ○ Hard card thickness up to 1.25 mm (0.05 in.)
Maximum Optical Resolution	600 dpi
Accessories & Consumables	<ul style="list-style-type: none"> ○ Stacking Deflector Accessory ○ Integrated A4/Legal Flatbed ○ Passport Flatbed Accessory ○ Carrier Sleeves (5 PACK) ○ Feed Roller Kit ○ Pre-Separation Pad & Roller Kit
Approvals and Product Certifications	<ul style="list-style-type: none"> ○ Argentina (S mark) ○ Australia/New Zealand (RCM) ○ Canada (cTUVus & ICES-003) ○ China (CCC) ○ European Union (CE) ○ European Union (GS Mark) ○ India (BIS) ○ Japan (VCCI) ○ Mexico (NOM) ○ Russia/Eurasian Economic Union (EAC) ○ South Korea (KC) ○ Taiwan (BSMI) ○ US (cTUVus & FCC)
Acoustical Noise	<ul style="list-style-type: none"> ○ Off or Ready mode: < 20 dB(A) ○ Scanning: <50 dB(A)
Barcode Reading	<ul style="list-style-type: none"> ○ Codabar ○ Code 128 ○ Code 3 of 9

- EAN-13
- EAN-8
- Interleaved 2 of 5
- PDF417
- QR
- UPC-A
- UPC-E

Bundled Software

Choose one and download from the web

- Capture Pro Limited Edition
- Smart Touch

Data Security

This scanner processes scanned data exclusively through volatile memory ensuring image data is effectively erased upon shut down. Read more about [data security](#).

Dimensions & Weight

Weight: 3.3 kg (7.2 lbs.) Depth: 204 mm (8.0 in.), not including input tray and output tray
Width: 312 mm (12.3 in.) Height: 182.5 mm (7.2 in.), not including input tray
Depth with Input Tray: 269 mm (10.6 in.)
Height with Input Tray: 231.6 mm (9.1 in.)

Electrical Requirements

100-240 V (International); 50-60 Hz

Environmental Certification

- 2008 EuP
- ENERGY STAR Qualified
- EPEAT Gold

File Format Outputs

- BMP
Native scanner and driver file format
- JPEG
Native scanner and driver file format
- Single-page TIFF
Native scanner and driver file format
- Microsoft Excel
available with bundled applications
- Microsoft Word
available with bundled applications
- Multipage TIFF
available with bundled applications
- PDF
available with bundled applications
- Text searchable PDF
available with bundled applications
- PNG
available with bundled applications
- RTF
available with bundled applications

Image Output Resolution Options

Up to 1200 dpi
Supported DPI: 75, 100, 150, 200, 240, 250, 260, 300, 400, 500, 600, 1200

Operating System Compatibility

- WINDOWS Server 2012 R2 X64 Editions
- WINDOWS Server 2016 X64 Editions
- WINDOWS 7 SP1 (32-bit and 64-bit)
- WINDOWS 8.1 (32-bit and 64-bit)
- WINDOWS 10 (32- and 64-bit)

- WINDOWS XP SP3 (32-bit and 64-bit) (available only in China)
- Ubuntu 16.04 64-bit and 32-bit
- Ubuntu 18.04 64-bit
- Open SUSE 11.3 (i586) 32-bit
- Open SUSE LEAP 15.1 64-bit
- SUSE Linux Enterprise Desktop 12.2 64-bit
- SUSE Linux Enterprise Desktop 15 SP1 for 64-bit
- Neokylin V7 (Intel x86/x64 & MIPS only) (Available only in China)
- UOS (MIPS only) (Available in China only)

Operator Control Panel	1.5 inch (38mm) Color Graphic Display
Optional Software	<ul style="list-style-type: none"> ○ Capture Pro Software ○ Info Input Solution
Operating Temperature / Operating Humidity	<ul style="list-style-type: none"> ○ Operating Temperature 10-35° C (50-95° F) ○ Operating Humidity 15% - 80% RH
Paper Handling (SurePath) Features	<ul style="list-style-type: none"> ○ Controlled stacking ○ Enhanced jam recovery ○ Intelligent Document Protection ○ Interactive multifeed with image display on host ○ Length Multifeed Detection ○ Ultrasonic Multifeed Technology ○ Operator overrides
Perfect Page Image Enhancement Software	<ul style="list-style-type: none"> ○ Adaptive threshold processing ○ Add or remove border ○ Aggressive cropping ○ Auto white balance ○ Autocrop ○ Automatic Brightness/Contrast ○ Automatic color balance ○ Automatic color detection ○ Automatic orientation ○ Automatic photo cropping ○ Background color smoothing ○ Barcode reading ○ Black and white image segmentation ○ Brightness and contrast adjustment ○ Content-based blank page removal ○ Deskew ○ Digital stamping ○ Dual stream scanning ○ Electronic color dropout ○ Enhanced color adjustment ○ Enhanced color management ○ Fixed cropping ○ Fixed thresholding ○ Halftone removal ○ Image edge fill ○ Image hole fill ○ Image merge ○ Image split ○ iThresholding

S2040 Scanner - Kodak Alaris

- Lone Pixel Noise Removal
- Long document scanning (up to 3000 mm/118 in.)
- Majority rule noise removal
- Multicolor dropout
- Multiple document output
- Orthogonal rotation
- Output Compression-CCITT Group IV, JPEG, Uncompressed Output
- Relative cropping
- Sharpening
- Sleeve scanning (for scanning A3 documents or multiple small documents)
- Streak filtering

Power Consumption

- Running: less than 36 watts
- Sleep Mode: less than 3.0 watts
- Standby: less than 0.5 watts

Standard Software And Drivers

- Citrix certified
- KOFAX certified
- ISIS Drivers
- LINUX (TWAIN and SANE) Drivers
- TWAIN Drivers
- WIA Drivers

Recommended Daily Volume

Up to 5,000 pages per day

Recommended PC Configuration

Minimum PC configuration with scanning application: Intel Core i3 processor or faster, at least 4 GB RAM (Microsoft Windows)

Scanning Technology

Dual RGB LED Illumination CIS (CMOS); Grayscale output bit depth is 256 levels (8-bit); color output bit depth is 24 bits (8 x 3); color capture bit depth is 48 bits (16 x 3)

Price

\$

* Throughput speed may vary depending on your choice of driver application software, operating system, PC and selected image processing features.

Warranty

Included warranty

3-Year Advanced Unit Replacement Plan

(AUR)

Same Model Replacement

Remote Support

Extended Warranty and Post-Warranty Options

Advanced Unit Replacement Plan

(AUR)

Next Business Day Response

Same Model Replacement

Remote Support

Professional services

Alaris offers an array of Professional Services. The Professional Services range from Technical Assistance offerings (e.g., Installation, Training) to Optimization Services (e.g., Capture Workflow Assessments) and more. To inquire or purchase, complete [the form below](#).

Contact

To contact us, complete our information request form below and we will get in touch with you soon.

Contact Type: (*)



I want information about the following product:

S2040 Scanner



First Name: (*)

Last name: (*)

Company: (*)

Job Role: (*)



Country: (*)



Email: (*)

Phone: (*)

Message:

(*) I agree to Kodak Alaris' Privacy Policy and allow Kodak Alaris sales representatives to contact me to answer my questions.

Click [here](#) to see [Kodak Alaris' Privacy Policy](#)

Yes, I'd also like to receive newsletters, tips and hints, articles, and product updates.

I'm not a robot reCAPTCHA
Privacy - Terms

Submit

[Privacy Policy](#) | [Legal / Site Terms](#)

© 2021 Kodak Alaris Inc. TM/MC/MR: Alaris, ScanMate. All trademarks and trade names used are property of their respective holders. The Kodak trademark and trade dress are used under license from Eastman Kodak Company.